

Surface Mount Superfast Recovery Rectifier
Reverse Voltage – 50 to 600 V
Forward Current – 1 A
FEATURES

- For surface mounted applications
- Low profile package
- Glass Passivated Chip Junction
- Superfast reverse recovery time
- Lead free in comply with EU RoHS 2011/65/EU directives


MECHANICAL DATA

- Case: SMBF
- Terminals: Solderable per MIL-STD-750, Method 2026
- Approx. Weight: 57mg / 0.002oz

Absolute Maximum Ratings and Characteristics

Ratings at 25 °C ambient temperature unless otherwise specified. Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

PINNING	
PIN	DESCRIPTION
1	Cathode
2	Anode




Simplified outline SMBF and symbol







Parameter	Symbols	ES1ABF	ES1BBF	ES1CBF	ES1DBF	ES1EBF	ES1GBF	ES1JBF	Units		
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	150	200	300	400	600	V		
Maximum RMS voltage	V _{RMS}	35	70	105	140	210	280	420	V		
Maximum DC Blocking Voltage	V _{DC}	50	100	150	200	300	400	600	V		
Maximum Average Forward Rectified Current at T _L = 100 °C	I _{F(AV)}	1						A			
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load (JEDEC Method)	I _{FSM}	35						A			
Maximum Forward Voltage at 1 A	V _F	1			1.25		1.65	V			
Maximum DC Reverse Current Ta = 25 °C at Rated DC Blocking Voltage Ta = 125 °C	I _R	5 100						µA			
Typical Junction Capacitance at V _R =4V, f=1MHz	C _j	10						pF			
Maximum Reverse Recovery Time ¹⁾	t _{rr}	35						ns			
Typical Thermal Resistance ²⁾	R _{θJA}	85						°C/W			
Operating and Storage Temperature Range	T _j , T _{stg}	-55 ~ +150						°C			

1) Measured with IF = 0.5 A, IR = 1 A, Irr = 0.25 A

 2) P.C.B. mounted with 0.5 X 0.5" (12.7 X 12.7 mm²) copper pad areas.

Fig.1 Reverse Recovery Time Characteristic And Test Circuit Diagram



Note: 1. Rise Time = 7ns, max.
 Input Impedance = 1megohm,22pF.
 2. Ries Time = 10ns, max.
 Source Impedance = 50 ohms.


Fig.2 Maximum Average Forward Current Rating

Fig.4 Typical Forward Characteristics

Fig.4 Maximum Non-Repetitive Peak Forward Surge Current

Fig.3 Typical Reverse Characteristics

Fig.5 Typical Junction Capacitance



PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SMBF



The recommended mounting pad size



Marking

Type number	Marking code
ES1ABF	E1AB
ES1BBF	E1BB
ES1CBF	E1CB
ES1DBF	E1DB
ES1EBF	E1EB
ES1GBF	E1GB
ES1JBF	E1JB